

Data



Efficiency in CT SOMATOM Emotion

2-Slice Configuration
syngo CT 2006A

SOMATOM Emotion – Standard Configuration

System Hardware	
0.8 s rotation time	●
Multislice UFC™ (Ultra Fast Ceramic) Detector	●
3.5 MHU X-ray tube	●
40 kW generator	●
CT patient table (200 kg/440 lbs table load)	●
Workplaces	
syngo® Acquisition Workplace*	●
19" (48 cm) monitor	●

CARE Applications	
CARE Filter	●
CARE Topo	●
CARE Dose4D™	●
System Software	
syngo Examination	●
syngo Viewing	●
syngo Filming	●
syngo Archiving & Network	●
syngo Dynamic Evaluation	●
syngo Service Solutions	●
Image Filter	●
SureView™	●
SOMATOM® LifeNet	●
Video Capture and Editing Tool	●
Applications	
Real-time MPR	●
syngo 3D SSD (Surface Shaded Display)	●
Volume Measurements	●
CT-Angiography	●

● Standard feature

* syngo, our unique multimodality software-platform brings together solutions for your clinical workflow. This complete integration is now evident in the consistent naming of our workplaces. syngo Acquisition Workplace replaces the Navigator. syngo CT Workplace replaces today's Wizard and syngo MultiModality Workplace replaces today's LEONARDO.

SOMATOM Emotion 2-slice configuration is registered/licenced as SOMATOM Emotion Duo

SOMATOM Emotion – Options

System Hardware	
Additional 19" (48 cm) monitor	○
Second 19" (48 cm) monitor with dual display functionality	○
Radiation Treatment Planning Enhancement	○
Workplaces	
syngo CT Workplace*	○
syngo MultiModality Workplace*	○
Additional 19" (48 cm) monitor	○
Second 19" (48 cm) monitor with dual display functionality	○
2 GB Volume Pro Graphics Accelerator	○
CARE Applications	
CARE Contrast CT	○
CARE Bolus CT	○
CARE Vision CT with HandCARE™	○
System Software	
Extended FOV (Field of View)	○
syngo Security Package	○
Siemens Virus Protection	○
Recon Card for syngo CT Workplace	○

syngo Applications	
syngo VRT	○
syngo InSpace4D	○
syngo Fly Through	○
syngo Dental CT	○
syngo Osteo CT	○
syngo Pulmo CT	○
syngo HeartView CT (prospective trigger)	○
syngo InSpace4D AVA (Advanced Vessel Analysis)**	○
syngo Calcium Scoring	○
syngo Neuro Perfusion CT	○
syngo Neuro DSA CT (Digital Subtraction Angiography)**	○
syngo Body Perfusion CT	○
syngo Colonography CT	○
syngo Colonography CT with PEV (Polyp Enhanced Viewing)**	○
syngo LungCARE CT	○
syngo LungCARE CT with NEV (Nodule Enhanced Viewing)	○
syngo Image Fusion	○
Respiratory Triggering CT	○

○ Optional feature

* syngo, our unique multimodality software-platform brings together solutions for your clinical workflow. This complete integration is now evident in the consistent naming of our workplaces. syngo Acquisition Workplace replaces the Navigator. syngo CT Workplace replaces today's Wizard and syngo MultiModality Workplace replaces today's LEONARDO.

** On syngo MultiModality Workplace only

SOMATOM Emotion – syngo CT.3D

syngo CT.3D	○
(on syngo CT Workplace*)	
<i>syngo CT Workplace*</i>	
<i>19" (48 cm) monitor</i>	
<i>2 GB Volume Pro Graphics Accelerator</i>	
<i>syngo 3D Basic</i>	
<i>syngo VRT</i>	
<i>syngo Fly Through</i>	
<i>syngo InSpace4D</i>	
<i>syngo Volume Calculation</i>	
<i>syngo Dynamic Evaluation</i>	

syngo CT.3D	○
(on syngo MultiModality Workplace*)	
<i>syngo MultiModality Workplace*</i>	
<i>19" (48 cm) monitor</i>	
<i>2 GB Volume Pro Graphics Accelerator</i>	
<i>syngo 3D Basic</i>	
<i>syngo VRT</i>	
<i>syngo Fly Through</i>	
<i>syngo InSpace4D</i>	
<i>syngo Volume Calculation</i>	
<i>syngo Dynamic Evaluation</i>	

○ *Optional feature*

* *syngo, our unique multimodality software-platform brings together solutions for your clinical workflow. This complete integration is now evident in the consistent naming of our workplaces. syngo Acquisition Workplace replaces the Navigator. syngo CT Workplace replaces today's Wizard and syngo MultiModality Workplace replaces today's LEONARDO.*

System Hardware

Gantry	
Aperture	70 cm
Scan field	50 cm
Tilt	$\pm 30^\circ$
Rotation time	0.8, 1.0, 1.5 s
Temporal resolution	down to 400 ms (syngo HeartView CT*)
Continuously rotating tube-detector unit with optimized geometry for high-resolution data acquisition across the entire scan field	
Data acquisition system	
Max. number of slices/rotation	2
Number of physical detector rows	2
Number of physical detector channels/slice	672
Total channels per slice	1,344
Number of projections	up to 1,500 (1/360°)
Sequence acquisition modes	2 x 1 mm, 2 x 1.5 mm, 2 x 2.5 mm, 2 x 4 mm, 2 x 5 mm, 1 x 2 mm 1 x 3 mm, 1 x 5 mm, 1 x 8 mm, 1 x 10 mm,
Spiral acquisition modes	2 x 1 mm, 2 x 1.5 mm, 2 x 2.5 mm, 2 x 4 mm, 2 x 5 mm
Speed and efficiency based on UFC (Ultra Fast Ceramic) detector with ultra short afterglow	
Designed to effectively suppress scattered radiation	

System Hardware

Tube assembly	
<i>Tube</i>	<i>DURA 352 MV High performance CT X-ray tube</i>
<i>Tube current range</i>	<i>30–240 mA</i>
<i>Tube voltage</i>	<i>80, 110, 130 kV</i>
<i>Tube anode heat storage capacity</i>	<i>3.5 MHU</i>
<i>Focal Spot size according to</i>	<i>0.8 x 0.4 mm/8° 0.8 x 0.7 mm/8°</i>
<i>IEC 60 336</i>	
<i>Computer controlled monitoring of anode temperature</i>	
<i>Multifan principle with Flying Focal Spot for all rotation times</i>	

CARE Filter	
<i>Al equivalent</i>	<i>tube: 6.4 mm Al</i>
<i>Beam limiting device</i>	<i>collimator: 0.15 mm Al equivalent</i>
Generator	
<i>Max. power</i>	<i>40 kW</i>
Patient table	
<i>Max. table load</i>	<i>200 kg/440 lbs</i>
<i>Table feed speed</i>	<i>1–100 mm/s</i>
<i>Vertical table travel range</i>	<i>45–83 cm (at table top) (17.7–32.7")</i>
<i>Vertical travel speed</i>	<i>≤ 22.4 mm/s</i>
<i>Scannable range</i>	<i>153 cm (60")</i>
<i>Distance between gantry front and table base</i>	<i>42 cm (16.5")</i>

syngo Workplaces

syngo Acquisition Workplace

The syngo Acquisition Workplace provides an intelligent and reliable workflow for data acquisition, image reconstruction, and routine postprocessing at the CT scanner. Built on the unique syngo platform, the syngo Acquisition Workplace is intuitive and user friendly.

High-performance computer

1 x Xeon 3.6 GHz processor

Graphics accelerator

NVIDIA graphics card for fast 3D postprocessing

Standard monitor

Flat screen 19" (48 cm) monitor

1,280 x 1,024 resolution

1,024 x 1,024 image display matrix

0.29 mm pixel size

Additional monitor*

Flat screen 19" (48 cm) monitor

Replication of primary monitor at remote location

Distance from host max. 30 m

Second monitor with dual display functionality*

Flat screen monitor 19" (48 cm)

Enables splitting of the syngo task cards onto two monitors. One monitor displays the viewing task card, for instance for the interactive review of images. All other syngo task cards are displayed on the second monitor.

RAM storage

2 GB

Image storage

146 GB; 240,000 uncompressed images

Additional storage

CD-R 700 MB; 1,100 images

MOD DICOM* 4.1 GB cartridge
6,500 images

External USB 2.0 disks for quick and easy raw data storage are supported

DICOM viewer

Included on each CD; automatically started on the viewer's PC

syngo Workplaces

syngo CT Workplace*

The syngo CT Workplace is a dedicated CT processing workplace that provides instant access to image and scan data via a shared database with the syngo Acquisition Workplace. With access to our comprehensive portfolio of CT clinical applications, the syngo CT Workplace can be customized to further enhance clinical performance. It can be networked via 1 GB LAN.

High-performance computer

2 x Xeon 3.6 GHz processor

Graphics accelerator

*NVIDIA graphics card for fast 3D postprocessing
Volume Pro Graphics Accelerator*;
2 GB on-board image memory additionally
accelerates applications*

Standard monitor

Flat screen 19" (48 cm) monitor

1,280 x 1,024 resolution

1,024 x 1,024 image display matrix

0.29 mm pixel size

Second monitor with dual display functionality*

Flat screen monitor 19" (48 cm)

Enables splitting of the syngo task cards onto two monitors. One monitor displays the viewing task card, for instance for the interactive review of images. All other syngo task cards are displayed on the second monitor.

RAM storage

2 GB

Image storage

Shared database with syngo Acquisition Workplace

Additional storage

CD-R Media 700 MB; 1,100 images

MOD DICOM 4.1 GB cartridge
6,500 images*

DICOM viewer

Included on each CD; automatically started on the viewer's PC

syngo Workplaces

syngo MultiModality Workplace*
<i>syngo MultiModality Workplace provides the unique advantage of an efficient multi-modality diagnostic workflow at a single workplace. Based on the unique syngo platform, it manages the clinical diagnostic workflow anywhere within the clinical environment. With the syngo MultiModality Workplace radiologists and clinicians benefit from access to our comprehensive syngo applications for Computed Tomography, Magnetic Resonance, PET and SPECT imaging, Angiography and Radiation Therapy Planning. The syngo MultiModality Workplace can be networked via 1 GB LAN.</i>
High-performance computer
<i>2 x Xeon 3.6 GHz processor</i>
Graphics accelerator
<i>NVIDIA graphics card for fast 3D postprocessing Volume Pro Graphics Accelerator*; 2 GB on-board image memory additionally accelerates applications</i>
Standard monitor
<i>Flat screen 19" (48 cm) monitor 1,280 x 1,024 resolution 1,024 x 1,024 image display matrix 0.29 mm pixel size</i>
Second monitor with dual display functionality*
<i>Flat screen monitor 19" (48 cm) Enables splitting of the syngo task cards onto two monitors. One monitor displays the viewing task card, for instance for the interactive review of images. All other syngo task cards are displayed on the second monitor.</i>

RAM storage
<i>6 GB</i>
RAID
<i>RAID 0 for enhanced read/write performance</i>
Image storage
<i>146 GB; 240,000 uncompressed images</i>
Additional storage
<i>CD-R Media 700 MB; 1,100 images DVD DICOM Drive 4.7 GB 8,400 images</i>
DICOM viewer
<i>Included on each CD; automatically started on the viewer's PC</i>

* Optional

CARE Applications

UFC Detector

Up to 30% dose reduction compared to conventional CT detectors.

High efficiency for low mAs requirements enable best possible image quality with low patient dose

Ultra short afterglow. Specially developed for sub-second and multislice applications.

SureView – Multislice Spiral Image Reconstruction

Brilliant image quality and dose savings up to 20% in spiral mode

CARE Filter

Specially designed X-ray exposure filter installed at the tube collimator. Up to 25% dose reduction with increased image quality.

CARE Contrast CT*

Facilitates contrast enhanced CT examinations

Enables the synchronization between scanning and contrast injection

One button control for easy use

Pediatric protocols

Special clinical protocols with 80 or 110 kV selection and a wide range of mAs settings. The X-ray exposure is adapted to the child's (and small adult's) weight and age, substantially reducing the effective patient dose.

CARE Topo

Real-time topogram

Manual interruption possible once desired anatomy has been imaged

CARE Dose4D – minimizing dose, maximizing quality – patient by patient

Automated real-time tube current adjustment for best diagnostic image quality at lowest possible dose, independent of patient size and anatomy

Fully automated dose management for adults and children with up to 68% dose reduction

CARE Bolus CT*

Scan mode for contrast bolus triggered data acquisition

Significant improvement of the planning procedure and diagnosis by enabling an optimum spiral scan start after contrast injection

The procedure is based on repetitive low dose monitoring scans at one slice level and analysis of the time density curve in a ROI (Region of Interest)

CARE Vision CT* with HandCARE

Perform interventions with real-time image guidance, including CT fluoroscopic mode.

Includes Real-time image guidance:

Image rate up to 8 frames/s

Image matrix 512 x 512

Foot switch. *Radiation release directly at the gantry.*

Additional monitor. *For parallel image display in the examination room.*

Flat screen 19" (48 cm) monitor

Distance from host max. 30 m

HandCARE. *Real-time dose modulation during the CT-guided intervention. The tube current is automatically switched off to avoid direct X-ray exposure to the physician's hands. HandCARE yields dose savings of up to 70% for the physician and up to 30% for the patient.*

System Software

Patient registration
Direct input of patient information on syngo
Acquisition Workplace immediately prior to scan
Pre-registration of patients at any time prior to scan
Special emergency patient registration (allows examination without entering patient data before scanning)
Patient information from HIS/RIS via DICOM Get Worklist
Transfer of examination information from scanner into HIS/RIS via MPPS (Modality Performed Procedure Step)
Protocols
Up to 10,000 protocols can be edited, modified and stored
Patient communication
Integrated patient intercom
Automatic Patient Instruction (API)
<ul style="list-style-type: none"> • Freely recordable • 30 API text pairs • Presets in nine languages available
Integrated display panel
Gantry front display showing current scan parameters such as kV, mA, scan time, table position, gantry tilt, and ECG trace**
Gantry front control panels
For convenient patient positioning (e.g. in case of trauma or interventional exams)
Gantry tilt control from the operator's console
Synchronized scanning and contrast injection*
CARE Contrast facilitates enhanced CT examinations through the hardware and software integration of CT scanner and injector
Three laser light markers
Coronal, sagittal, and axial laser light, that show the isocentric position of the scan plane. With RTP (Radiation Treatment Planning) Enhancement, the laser lights can be easily adjusted.***

Topogram	
Length	128–1,024 mm (5–40.3")
Scan times	1.5–11.2 s
Views	a.p., p.a., lateral
CARE Topo	
Real-time topogram	
Manual interruption possible once desired anatomy has been imaged	
Sequence Acquisition	
Reconstructed slice widths	1.0, 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 8.0, 10.0
Scan times	0.8, 1.0, 1.5 s (± 5%)
full scan (360°)	
Partial scan times (240°)	0.53, 0.67 s (± 5%)
No. of uninterrupted scans per range	99
No. of ranges in autorange	8
Standard scan cycle time	2.5 s (± 10%) at 1.0 s scan time
Acquisition with or without table feed	
Automatic clustering of scans	
Dynamic Multiscan:	
Multiple (continuous) sequence scanning without table movement for fast dynamic contrast studies	
Dynamic scan cycle time	1.2 s (± 10%) at 0.8 s scan time
	1.5 s (± 10%) at 1.0 s scan time
Patient breath-hold time indicator	
Patient-friendly display at the back of the gantry for indication of the remaining breath-hold time	
Automatic patient positioning	
Two user-configurable buttons on the gantry panel	
One touch, quick patient positioning for pre-selected clinical protocols – e.g. head, thorax	

* Optional
 ** Requires syngo HeartView CT
 *** Optional for RTP

System Software

Multislice Spiral Acquisition	
Reconstructed slice widths	1.0, 1.25, 2.0, 3.0, 5.0, 6.0, 8.0, 10.0 mm
Scan times full scan (360°)	0.8, 1.0, 1.5 s
Reconstruction increment	0.1–10 mm
Pitch factor	0.5–2.0
Volume pitch	1.0–4.0
Spiral scan time	max. 100 s
Scan length	max. 150 cm (59")
Extended Field of View*	
Special image reconstruction algorithms that provide visualization of objects using a FOV up to 70 cm**	

SureView: Siemens' patented solution for Multislice CT reconstruction

Excellent for clinical workflow:
Forget about compromises in your clinical workflow. Just specify the slice thickness in your protocols according to your clinical needs. SureView automatically takes care of providing excellent volume image quality – with exceptional performance.

Multiply your clinical performance with SureView:
High-quality imaging at any scanning speed. SureView allows the CT scanner to automatically select the necessary pitch value to achieve the coverage and scan time defined by you, while keeping selected slice thickness.

* Optional

** The image quality for the area outside the standard 50 cm scan field does not meet the image quality specifications shown in the technical data sheet and image artifacts may appear, depending on the anatomy scanned

System Software

Image reconstruction	
<i>Real-time display</i>	<i>Real-time image display (512 x 512) during spiral acquisition</i>
<i>Slice thickness</i>	<i>1.0–10.0 mm</i>
<i>Scan field</i>	<i>50 cm</i>
<i>Recon field</i>	<i>5–50 cm, 5–70 cm with extended FOV*</i>
<i>Standard recon time</i>	<i>up to 5 images/s</i>
<i>Recon matrix</i>	<i>512 x 512</i>
<i>HU scale</i>	<i>–1,024 to +3,071</i>
<i>Extended HU scale</i>	<i>–10,240 to +30,710</i>
<i>Wide range of selectable slice thickness for prospective selection and/or retrospective reconstruction for spiral scans</i>	
<i>Real-time image display in 512 x 512 matrix parallel to spiral acquisition (e.g. for trauma)</i>	
CINE display	
<i>Display of image sequences</i>	
<i>Automatic or interactive with mouse control</i>	
<i>Max. image rate</i>	<i>10 frames/s</i>
Windowing	
<i>Window width and center freely selectable</i>	
<i>Single window</i>	
<i>Double window (e.g. bone/soft tissue)</i>	
<i>Multiple window settings for multi-image display</i>	
<i>Organ-specific window settings, e.g. for soft tissue and bones</i>	

Filming	
<i>Digital film documentation; connection to suitable digital camera</i>	
<i>Connection via DICOM Basic print</i>	
<i>Automatic filming</i>	
<i>Interactive virtual film sheet</i>	
<i>Customizable film formats with up to 64 images</i>	
<i>Filming parallel to other activities</i>	
<i>Independent scanning and documentation</i>	
<i>Freely selectable positioning of images onto film sheet</i>	
<i>Configurable image text</i>	
Printing	
<i>Documentation on postscript printer supported</i>	
Image transfer/Networking	
<i>Interface for transfer of medical images and information using the DICOM standard. Facilitates communication with devices from different manufacturers.</i>	
<i>DICOM Storage (Send/Receive)</i>	
<i>DICOM Query/Retrieve</i>	
<i>DICOM Basic print</i>	
<i>DICOM Get Worklist (HIS/RIS)</i>	
<i>DICOM MPPS</i>	
<i>DICOM Storage Commitment</i>	
<i>DICOM Viewer on CD</i>	
Raw data	
<i>Drive size</i>	<i>65 GB</i>
<i>Capacity</i>	<i>12,000 scan-seconds</i>
<i>External USB 2.0 disks for quick and easy raw data storage are supported</i>	

* Optional; reconstruction area outside the standard 50 cm FOV is for visualization purposes only and is not of diagnostic image quality

System Software

Evaluation tools

Parallel evaluation of more than 10 Regions of Interest

- Circle
- Irregular
- Polygonal

Statistical evaluation

- Area/Volume
- Standard deviation
- Mean value
- Min./max. values
- Histogram

Profile cuts

- Horizontal
- Vertical
- Oblique

Distance measurement

Angle measurement

Online measurement of a 5 x 5 pixel size ROI

Freely selectable positioning of coordinate system

Crosshair

Image annotation and labeling

syngo Dynamic Evaluation

Evaluation of contrast enhancement in organs and tissues

Calculation of

- Time-density curves (up to 5 ROI's)
- Peak-enhancement images
- Time-to-peak images

Video Capture and Editing Tool

Integrated solution for imaging and visualization of 4D information, allowing the generation and editing of video files for improved diagnoses, recording, and teaching. A wide range of multimedia formats are supported, e.g. AVI, Flash (SWF), GIF, QuickTime (MOV), streaming video.

2D postprocessing

Image zoom and pan

Image manipulations

- Averaging, subtraction
- Reversal of gray-scale values
- Mirroring

Advanced image algorithms

- Posterior Fossa Optimization for reduction of beam hardening artifacts in head images
- Low Contrast Enhancement for improving low contrast detectability
- High Contrast Enhancement for increased sharpness of high contrast structures
- Advanced Smoothing Algorithm edge preserving and smoothing filter, dedicated to cardiac exams

syngo Security Package*

Provides functionality for user management and flexible access control for patient data

Siemens Virus Protection*

Offers top-level defense in safeguarding CT systems against viruses

Image Quality

Low-contrast resolution	
<i>Low-contrast resolution is the ability to see</i>	
<ul style="list-style-type: none"> • a small object (mm) • with a certain contrast difference (HU) • on a particular phantom (Ø) • at a certain mAs value (mAs) • with a particular patient dose (mGy) 	
Phantom	CATPHAN (16 cm)
Object size	3 mm
Contrast difference	3 HU
Dose at the surface	19.7 mGy* at 100 mAs
Technique	1.0 s/0.8 s, 10 mm, 130 kV
Phantom	CATPHAN (20 cm)
Object size	5 mm
Contrast difference	3 HU
Dose at the surface	15.8 mGy* at 90 mAs
Technique	1.0 s/0.8 s, 10 mm, 130 kV

High-contrast resolution			
0% MTF ($\pm 10\%$)	15.5 lp/cm, 0.32 mm		
2% MTF ($\pm 10\%$)	14.0 lp/cm, 0.36 mm		
10% MTF ($\pm 10\%$)	12.3 lp/cm, 0.41 mm		
50% MTF ($\pm 10\%$)	9.0 lp/cm, 0.56 mm		
Technique	Tungsten wire in air 60 mAs, 130 kV, 1.0 s/0.8 s, 1.0 mm		
Homogeneity			
Cross-field uniformity in a 20 cm water phantom	max. ± 4 HU typ. ± 2 HU		
Phantom positioned near center of rotation			
Dose, CTDI₁₀₀ values*			
Phantom Ø		110 kV	130 kV
		mGy/100 mAs	
16 cm	A	14.4	21.7
	B	15.7	23.3
32 cm	A	4.2	6.7
	B	8.4	12.8
A: at center	B: 1 cm below surface		
Technique	PMMA-Phantom Absorbed dose for reference material air Max. deviation $\pm 30\%$ Expected deviation 15% Slice > 1 mm		

* Air KERMA, measured on the surface of the phantom with max. deviation $\pm 30\%$

Applications

Real-time MPR

Real-time multiplanar reformatting of secondary views

Variable slice thickness (MPR thick, MPR thin) and distance with configurable default values

Viewing perspectives

- *Sagittal*
- *Coronal*
- *Oblique*
- *Double oblique*
- *Freehand (curvilinear)*

syngo 3D SSD (Surface Shaded Display)

Three-dimensional display of surfaces with different density values

- *Soft tissue*
- *Bone*
- *Contrast-enhanced vessels*

Volume measurements

Measurements of various tissues and organs with HU-based region growth algorithms and interactive ROI definition

syngo VRT (Volume Rendering Technique)

Advanced 3D application package for the optimal display and differentiation of different organs through independent control of color, opacity, and shading in up to 4 tissue classes

CT-Angiography

MIP: Maximum Intensity Projection

MinIP: Minimum Intensity Projection

Thin MIP function for projection within a small slab to focus on particular vascular structure

Evaluation of spiral images and display of vessels, vascular anomalies, aneurysms, plaques, and stenoses

syngo InSpace4D* – real-time interactive evaluation, in space and time

One-click bone removal

Automated segmentation and removal of bony structures for vascular analysis

High performance volume reading for physician's diagnosis and pre-surgical planning in daily clinical routine

syngo Fly Through*

Virtual Endoscopy software enabling visualization of vessels, airways, and the intestines

syngo Dental CT*

Reformatting of panoramic slices and paraxial sections through the lower and upper jaw for analysis in connection with implantation surgery

syngo Osteo CT*

Non-invasive measurement of the bone mineral density of the lumbar spine to help early diagnosis of osteopenia and osteoporosis, and to assess the effectiveness of treatment

Osteo CT measurements are standardized to the ESP Phantom (ESP: European Spine Phantom)

Includes table mat and reference Phantom for Osteo CT studies

syngo Pulmo CT*

Quantitatively evaluates lung density and structure to help early diagnosis and treatment of lung disease and surgical intervention planning

syngo HeartView CT*

ECG-synchronized acquisition using prospective ECG triggered mode

Basis for 3D cardiac reconstructions, e.g. CT-Angiography of the coronary vessels and Calcium Scoring

The ECG signal used for triggering the CT images is acquired by an integrated ECG device. The ECG signal is displayed on the gantry front cover.

Applications

syngo InSpace4D AVA (Advanced Vessel Analysis)**
<i>Optional plug-in for syngo InSpace4D</i>
<i>Dedicated syngo-based application for analysis of vessel lesions</i>
<i>Automatic vessel segmentation plus accurate quantification of vascular lesions. Compatible with CT and MR datasets.</i>
syngo Calcium Scoring*
<i>Displays the quantity and distribution of coronary calcification for the diagnosis and treatment of cardiac disease</i>
syngo Neuro Perfusion CT*
<i>Evaluates dynamic CT data of the brain. Used for the early differential diagnosis of acute ischemic stroke. Additionally, it allows imaging of blood brain barrier disruptions in brain tumors.</i>
syngo Neuro DSA CT (Digital Subtraction Angiography)**
<i>A fully automated workflow, facilitates optimal visualization and evaluation of complex intracranial vascular structures and helps to delineate aneurysms and other vascular diseases</i>
syngo Colonography CT*
<i>For non-invasive visualization and quantitative evaluation of colon polyps</i>
<i>Enables real-time virtual 3D endoluminal viewing</i>
syngo Colonography CT with PEV (Polyp Enhanced Viewing)**
<i>Computer-assisted identification of polyps with virtual second reader support</i>

syngo LungCARE CT*
<i>Software for fast 3D-based visualization and quantitative evaluation of lung nodules, with lowest possible radiation dose. Includes fully automated follow-up.</i>
syngo LungCARE CT with NEV (Nodule Enhanced Viewing)*
<i>Provides computer supported identification of lung nodules. Functions as a second reader opinion.</i>
syngo Body Perfusion CT*
<i>For functional analysis of organs and tumors. Useful for interventional procedures and radiation therapy monitoring and planning.</i>
syngo Image Fusion*
<i>Registration and composite display of CT, MR, NM, and PET images. Provides for optimal physician's diagnosis by fusion of morphological data with functional information.</i>
RTP Enhancement*
<i>Hardware and software components to optimize the RTP process</i>
Respiratory Triggering CT*
<i>Hardware and software components that allow for the capture and storage of a patient's respiratory signal data during a triggered sequence acquisition</i>
<i>Organ motion artifacts caused by respiration are minimized or eliminated and better accuracy is obtained regarding organ position, size, and volume</i>

* Optional

** Optional on syngo MultiModality Workplace only

Installation

Dimensions	Height (mm/inch)	Width (mm/inch)	Length (mm/inch)	Weight (kg/lbs)
Components				
<i>Gantry</i>	≤ 1,780 / 70,1	≤ 790; 680 / 31.1; 26,7	≤ 2,320 / 91,3	≤ 1,200 / 2,640
<i>Patient table</i>	≤ 940 / 37,0	≤ 680 / 26,7	≤ 2,230 / 87,8	≤ 430 / 946
<i>Operator's console*</i>	≤ 700 / 27,5	≤ 800 / 31,5	≤ 1,400 / 55,1	≤ 60 / 132
<i>UPS</i>	≤ 160 / 6,3	≤ 250 / 9,8	≤ 560 / 22,1	≤ 20 / 44
<i>Image reconstruction system</i>	≤ 445 / 17,5	≤ 205 / 8,1	≤ 560 / 22,1	≤ 30 / 66
Computer system				
<i>syngo Acquisition Workplace</i>	≤ 445 / 17,5	≤ 205 / 8,1	≤ 560 / 22,1	≤ 30 / 66
<i>syngo CT Workplace</i>	≤ 445 / 17,5	≤ 205 / 8,1	≤ 560 / 22,1	≤ 30 / 66

* Includes monitor, keyboard, mouse, scan control box, and operator's desk (optional)

Installation

Power supply	
Nominal voltage $\pm 10\%$	190–480 V
Nominal line frequency $\pm 10\%$	50; 60 Hz
Max. power consumption	≤ 48 kVA
Power consumption	≤ 1.0 kW standby
Mean power consumption	≤ 4.7 kW scanning
Protection against input power instability	
X-ray	20 ms
Controllers	300 ms
Computer	3 min
Frequency stability $\pm 5\%$	50; 60 Hz

Electromagnetic compatibility		
<i>This product is in compliance with IEC 60601-1-2 and fulfills CISPR 11 Class A</i>		
Examination room environment		
Temperature range	18–30 °C	
Relative air humidity without condensation	20–85%	
Heat dissipation (Gantry)	≤ 4.7 kW scanning ≤ 1.5 kW standby	
Heat dissipation (Computer)	≤ 0.9 kW	
Surface area for installation		
	min.*	recommended
Complete system	18.5 m ²	22.0 m ²
Gantry & table only	15.5 m ²	17.0 m ²

On account of certain regional limitations of sales rights and service availability, we cannot guarantee that all products included in this brochure are available through the Siemens sales organization worldwide. Availability and packaging may vary by country and is subject to change without prior notice. Some/All of the features and products described herein may not be available in the United States.

The information in this document contains general technical descriptions of specifications and options as well as standard and optional features which do not always have to be present in individual cases.

Siemens reserves the right to modify the design, packaging, specifications and options described herein without prior notice. Please contact your local Siemens sales representative for the most current information.

Note: Any technical data contained in this document may vary within defined tolerances. Original images always lose a certain amount of detail when reproduced.

The statements contained herein are based on the actual experience of Siemens customers. Siemens maintains data on file to support these claims. However, these statements do not suggest or constitute a warranty that all product experience will yield similar results. Results may vary, based on the particular circumstances of individual sites and users.

Please find fitting accessories:
www.siemens.com/medical-accessories

Siemens AG
Wittelsbacherplatz 2
D-80333 Munich
Germany

Headquarters

Siemens AG, Medical Solutions
Henkestr. 127, D-91052 Erlangen
Germany
Telephone: +49 9131 84-0
www.siemens.com/medical

Contact Address

Siemens AG, Medical Solutions
Computed Tomography
Siemensstr. 1, D-91301 Forchheim
Germany
Telephone: +49 9191 18-0

Siemens **Medical**
Solutions that help